

5 Conclusion

In this paper, the attitude control of the quadrotor system is controlled. Roll and pitch angles are controlled by PD and time-delayed control methods. Their control performances are compared empirically. The time-delayed control method shows the outperformed control performance over the PD control method, especially when the disturbance is applied to the system. The time-delayed control method can be applied to the hovering control of the quadrotor system in the future.

Acknowledgments. The research has been supported by the 2013 Korea Research Foundation and the center for autonomous intelligent manipulation (AIM) for service robots of the MKE (The Ministry of Knowledge Economy), Korea, under the Human Resources Development Program for Convergence Robot Specialists support program supervised by the NIPA (National IT Industry Promotion Agency) under NIPA-2013-H1502-13-1001.

References

1. Oner, K.T., Cetinsoy, E., Unel, M., Aksit, M.F., Kandemir, I., Gulez, K.: Dynamic model and control of a new quad-rotor unmanned aerial vehicle with tilt-wing mechanism. *World Academy of Science, Engineering and Technology* 45, 58–63 (2008)
2. Jeong, S.H., Jung, S.: Novel design and position control of an omni-directional flying automobile (Omni-flymobile). In: ICCAS, pp. 2480–2484 (2010)
3. Huang, H., Hoffmann, G.M., Waslander, S.L., Tomlin, C.J.: Aerodynamics and control of autonomous quad-rotor helicopters in aggressive maneuvering. In: *IEEE Conf. on Robotics and Automations*, pp. 3277–3282 (2009)
4. Dierks, T., Jagannathan, S.: Output feedback control of a quad-rotor UAV using neural networks. *IEEE Trans. on Neural Networks* 21(1), 50–66 (2010)
5. Jeong, S.H., Jung, S., Tomizuka, M.: Attitude Control of a Quad-rotor System Using an Acceleration-based Disturbance Observer: An Empirical Approach. In: AIM, pp. 916–921 (2012)